



- Designed for simple museum AV control applications
- Controls 20 devices (expandable up to 50 devices)
- Easily build AV automation, including time of day scheduling
- One universe of Art-Net or sACN lighting control
- Serves one WebPanel user interface to any device with a web browser

This capable and flexible device is suited to simple AV control applications and installation types. Its ruggedised, fanless, small form factor makes it easy to mount where AV racks aren't suitable. Showmaster Mini carries a reduced-feature version of Medialon Manager show control software, making it a low-cost solution that still carries the power, flexibility, and ease of use Medialon is known for.

Medialon Show Controller

Designed for less demanding applications, it starts with a 20-device limitation, expandable in 10-device batches up to a max of 50 devices. This show controller runs Medialon Manager V7.1 for Showmaster Mini, which in comparison means:

- no Timelines, Step-based tasks only
- 1 × WebPanel connection (not expandable)
- no Timecode or MIDI resources
- 1 Universe of Art-Net or sACN lighting control (in or out)

AV Control, Simplified.

Sometimes all you need to do is schedule and automate your AV system's daily power-up and shutdown sequences, or have a tablet interface for managing media on a video wall, but you don't need all the bells and whistles of a full show control solution. Showmaster Mini is ideal for these simple applications, and is compatible with other Medialon products so it can work as a sub-system controller under the scope of a larger Medialon system.

Low power, small form factor

Showmaster Mini uses Advantech industrial automation hardware, built for long-term use in demanding environments. Its fanless design means no moving parts to replace, and it's tiny form factor allows you to save rack space for equipment that needs it; Showmaster Mini can be DIN rail mounted with the included mounting brackets, meaning you can put it almost anywhere.

Product Specifications Showmaster Mini

USB ports	4 × USB 3.0
Serial ports	2 × RS232
Video output	2 × HDMI UHD
Audio	1 × mic in, 1 × line out, 3.5 mm mini jack
Ethernet	2 × 10/100/1000 base-T
Storage	238 GB SSD
Operating environment	−30 to +70 C
Power connection	12-28 VDC 60 W (3 pin Phoenix connector)
Power consumption	7.6 W typical, 19 W max.
Mounting options	DIN-rail/Wall Mount
Dimensions (W × D × H)	158 mm × 114 mm × 53.5 mm (6-1/4" × 4-1/2" × 2-1/8")
Weight	1.2 kg (2.65 lbs)



Technical specifications are subject to change without prior notice. Please check www.medialon.com for the latest information.

Last updated: September 2023

7thSense Design Ltd
2 The Courtyard Shoreham Road
Upper Beeding
Steyning
West Sussex
BN44 3TN
UK

7thSense – London
The Record Hall
16-16A Baldwin's Gardens
Farringdon
London
EC1N 7RJ
UK

7thSense LLC – Orlando
4207 Vineland Road
Suite M1
Orlando
FL 32811
USA

